

*Remove the cane shaft before installing.
Refer to your AR-CANE Instruction Manual for shaft removal.*

01

IDENTIFY CORRECT END

*Locate the heat shrink end —
opposite the silicone end cap.
This is the end that inserts into
the handle.*



02

INSERT INTO HANDLE

*Insert the heat shrink end into
the shaft opening and push
until fully seated in the interior
accessory pocket adjacent to
the set screw.*



03

TIGHTEN SET SCREW

*Using the included 1/8" hex
wrench, tighten the accessory
retention set screw until snug
against the baton. Do not
overtighten.*



01

REMOVE DETENT PIN

Pull the stainless ball detent pin completely clear of the handle.



02

EXTRACT BATON

Grasp the cane shaft with one hand and pull the handle free with the other. The baton deploys with the handle.



03

FULL DEPLOYMENT

Flexible baton is now fully deployed and ready for use.



Scan for instructions & product updates
www.ar-cane.com/support

SAFETY & DISCLAIMER

THE AR-CANE Flexible Baton is a walking aid accessory. • Not a firearm or firearm accessory. • Use responsibly and in accordance with all applicable laws and regulations. • Users are responsible for verifying compliance with all applicable state and local laws regarding carry and use. • For questions or assistance: info@ar-cane.com